

Conductivity Electrode

innoSens 320/330/350

The innoSens range of conductivity electrode offers durability, reliability and high performance for a wide range of conductivity monitoring applications, from ultrapure water to sewage and wastewater treatment.

innoSens 320-0.01 Conductivity Electrode	Order No.: 35-0320-01 	Measuring range 0.01–200.0µS/cm Temperature probe PT1000 Working temp 0–100°C Max. Pressure 6bar Installation Pipe installation Connection method 3/4" NPT Cable length 10m standard Two-stage electrode, 316L material, suitable for pure water, ultrapure water
innoSens 320-0.1 Conductivity Electrode	Order No.: 35-0320-02 	Measuring range 0.1–2000µS/cm Temperature probe PT1000 Working temp 0–100°C Max. Pressure 6bar Installation Pipe installation Connection method 3/4" NPT Cable length 10m standard Two-stage electrode, 316L material, suitable for raw water, pure water
innoSens 330 Conductivity Electrode	Order No.: 35-0330-00 	Measuring range 0–200mS/cm Temperature probe PT1000 Working temp 0–100°C Max. Pressure 6bar Installation Pipe installation Connection method 3/4" NPT Cable length 10m standard Four-stage electrode, PPS material, suitable for tap water, sewage
innoSens 350-0.01 Conductivity Electrode	Order No.: 35-0350-01 	Measuring range 0.01–200.0µS/cm Temperature probe PT1000 Working temp 0–100°C(Optional 0–135°C) Max. Pressure 6bar Installation Pipe installation Connection method Chucks Cable length 10m standard Two-stage electrode, 316L material, suitable for pure water, ultrapure water
innoSens 350-0.1 Conductivity Electrode	Order No.: 35-0350-02 	Measuring range 0.1–2000µS/cm Temperature probe PT1000 Working temp 0–100°C(Optional 0–135°C) Max. Pressure 6bar Installation Pipe installation Connection method Chucks Cable length 10m standard Two-stage electrode, 316L material, suitable for raw water, pure water
innoSens 350-10 Conductivity Electrode	Order No.: 35-0350-03 	Measuring range 0–200mS/cm Temperature probe PT1000 Working temp 0–135°C Max. Pressure 6bar Installation Pipe installation Connection method Chucks Cable length 10m standard Four-stage electrode, 316L/PEEK material, suitable for medium water, etc.